



Model No.	Dimensions of Assembly (mm)			Dimensions of block (mm)										Dimensions of rail (mm)										Mounting Bolt for rail (mm)	Basic Static Load Rating C (kN)	Basic Dynamic Load Rating C0 (kN)	Static Rated Moment			Weight		Stock
	H	H1	N	W	B	B1	C	L1	L	K1	G	M x L	T	H2	H3	W8	Hr	D	h	d	P	E	MR				MP	MY	Block kg	Rail kg/m		
HGL15CA	24	4.3	9.5	34	26	4	26	39.4	61.4	10	5.3	M4x4	6	3.95	3.7	15	15	7.5	5.3	4.5	60	20	M4 x 16	11.38	25.31	0.17	0.15	0.15	0.14	1.45	o	
HGL25CA	36	5.5	12.5	48	35	6.5	35	58	84	16.8	12	M6x6	8	6	9	23	22	11	9	7	60	20	M6 x 20	26.48	56.19	0.64	0.51	0.51	0.42	3.21	o	
HGL25HA							50	78.6	104.6	19.6															32.75	76.00	0.87	0.88	0.88	0.57	o	
HGL30CA	42	6	16	60	40	10	40	70	97.4	20.25	12	M8x10	8.5	6.5	10.8	28	26	14	12	9	80	20	M8 x 25	38.74	83.06	1.06	0.85	0.85	0.78	4.47	o	
HGL30HA							60	93	120.4	21.75															47.27	110.13	1.40	1.47	1.47	1.03	o	
HGL35CA	48	7.5	18	70	50	10	50	80	112.4	20.6	12	M8x12	10.2	9	12.6	34	29	14	12	9	80	20	M8 x 25	49.52	102.87	1.73	1.20	1.20	1.14	6.30	o	
HGL35HA							72	105.8	138.2	22.5															60.21	136.31	2.29	2.08	2.08	1.52	o	
HGL45CA	60	9.5	20.5	86	60	13	60	97	139.4	23	12.9	M10x17	16	8.5	20.5	45	38	20	17	14	105	22.5	M12 x 35	77.57	155.93	3.01	2.35	2.35	2.08	10.41	o	
HGL45HA							80	128.8	171.2	28.9															94.54	207.12	4.00	4.07	4.07	2.75	o	
HGL55CA	70	13	23.5	100	75	12.5	75	117.7	166.7	27.35	12.9	M12x18	17.5	12	19	53	44	23	20	16	120	30	M14 x 45	114.44	227.81	5.66	4.06	4.06	3.25	15.08	o	
HGL55HA							95	155.8	204.8	36.4															139.35	301.26	7.49	7.01	7.01	4.27	o	

Note: 1 kgf = 9.81 N

LINEARIKELKAT HGL

Tuotekoodi	Tuotenimi
2.1031	HGL15CA
2.1032	HGL20CA
2.1033	HGL25CA
2.1034	HGL30CA
2.1035	HGL35CA
2.1036	HGL45CA
2.1037	HGL55CA

Tuotekoodi	Tuotenimi
2.1038	HGL65CA
2.1039	HGL25HA
2.1040	HGL30HA
2.1041	HGL35HA
2.1042	HGL45HA
2.1043	HGL55HA